

序号	我司型号	规格	模块大小	显示尺寸	电压	接口	控制器	尺寸	显示颜色	工作温度	备注
1	CXO0801A	8*1	54.80 × 8.00 × 2.00	17.18 × 3.18	3.3V	并口/IIC/SPI	US2011	0.69寸	黄、白	-40℃-85℃	
2	CXO0802A	8*2	69.75 × 16.40 × 2.00	27.81 × 11.50	3.3V	并口/IIC/SPI	US2011	1.20寸	黄、白	-40℃-85℃	
3	CXO1601A	16*1	68.11 × 14.44 × 2.00	59.62 × 6.56	3.3V	并口/IIC/SPI	US2011	2.36寸	黄、白	-40℃-85℃	
4	CXO1602A	16*2	75.39 × 12.20 × 2.00	34.10 × 7.40	3.3V	并口/IIC/SPI	US2011	1.37寸	黄、白	-40℃-85℃	
5	CXO1602B	16*2	98.64 × 17.10 × 2.00	56.22 × 11.52	3.3V	并口/IIC/SPI	US2011	2.26寸	黄、白	-40℃-85℃	
6	CXO1602C	16*2	141.80 × 26.50 × 2.00	91.14 × 18.98	3.3V	并口/IIC/SPI	US2066	3.67寸	蓝红白黄绿	-40℃-85℃	
7	CXO1604A	16*4	99.54 × 26.00 × 2.00	56.20 × 20.80	3.3V	并口/IIC/SPI	US2011	2.36寸	黄、白	-40℃-85℃	
8	CXO2002A	20*2	115.04 × 17.03 × 2.00	73.52 × 11.52	3.3V	并口/IIC/SPI	US2011	2.92寸	黄、白	-40℃-85℃	
9	CXO2004A	20*4	113.54 × 25.60 × 2.00	70.42 × 20.82	3.3V	并口/IIC/SPI	US2011	2.89寸	黄、白	-40℃-85℃	
10	CXO4002A	40*2	235.20 × 18.30 × 2.00	147.50 × 11.50	3.3V	并口/IIC/SPI	US2011	5.8寸	黄、白	-40℃-85℃	
11	CXO6432A	64*32	14.50 × 21.60 × 1.20	11.18 × 5.58	3.3V	并口/IIC/SPI	SH1106	0.49寸	黄、白	-40℃-85℃	
12	CXO6448A	64*48	18.46 × 27.90 × 1.45	13.42 × 10.06	3.3V	并口/IIC/SPI	SSD1306	0.66寸	黄、白	-40℃-85℃	
13	CXO7232A	72*32	14.90 × 22.09 × 1.21	11.212 × 4.972	3.3V	并口/IIC/SPI	SSD1306	0.48寸	白	-40℃-85℃	
14	CXO7240A	72*40	12.00 × 23.00 × 1.50	9.196 × 5.18	3.3V	并口/IIC/SPI	SH1106	0.42寸	白	-40℃-85℃	
15	CXO9616A	96*16	36.80 × 9.00 × 1.30	17.26 × 3.18	3.3V	并口/IIC/SPI	SSD1306	0.69寸	白	-40℃-85℃	
16	CXO9616B	96*16	38.10 × 9.20 × 1.30	21.104 × 3.504	3.3V	并口/IIC/SPI	SSD1306	0.84寸	蓝、白、绿	-40℃-85℃	
17	CXO9639A	96*39	23.80 × 26.00 × 1.30	19.372 × 7.858	3.3V	并口/IIC/SPI	SSD1306	0.82寸	黄、白	-40℃-85℃	
18	CXO9664A	96*64	24.90 × 32.75 × 1.40	19.953 × 13.424	3.3V	并口/IIC/SPI	SSD1305	0.95寸	黄、白	-40℃-85℃	
19	CXO12832A	128*32	45.30 × 8.70 × 1.20	21.356 × 5.324	3.3V	并口/IIC/SPI	SSD1316	0.87寸	白	-40℃-85℃	
20	CXO12832B	128*32	46.30 × 8.90 × 1.40	22.38 × 5.58	3.3V	并口/IIC/SPI	SSD1316	0.91寸	白	-40℃-85℃	
21	CXO12832C	128*32	29.80 × 26.50 × 1.30	25.58 × 6.38	3.3V	并口/IIC/SPI	SSD1306	1.04寸	蓝、白	-40℃-85℃	
22	CXO12832D	128*32	50.50 × 15.75 × 2.00	42.22 × 10.54	3.3V	并口/IIC/SPI	SSD1307	1.71寸	橙	-40℃-85℃	
23	CXO12832E	128*32	62.00 × 60.00 × 2.00	55.02 × 13.10	3.3V	并口/IIC/SPI	SSD1309	2.23寸	蓝、黄、白	-40℃-85℃	
24	CXO64128A	64*128	14.00 × 39.30 × 1.20	10.86 × 21.74	3.3V	并口/IIC/SPI	SH1107	0.96寸	白	-40℃-85℃	
25	CXO12864A	128*64	26.70 × 31.26 × 1.45	21.744 × 10.864	3.3V	并口/IIC/SPI	SSD1306	0.96寸	蓝、白	-40℃-85℃	
26	CXO12864B	128*64	34.50 × 35.00 × 1.45	29.42 × 14.70	3.3V	并口/IIC/SPI	SSD1306	1.30寸	蓝、白	-40℃-85℃	
27	CXO12864C	128*64	42.04 × 63.22 × 1.45	35.052 × 17.516	3.3V	并口/IIC/SPI	SSD1309	1.54寸	蓝、黄、白	-40℃-85℃	
28	CXO12864D	128*64	60.50 × 73.00 × 2.00	55.01 × 27.49	3.3V	并口/IIC/SPI	SSD1309	2.42寸	蓝、黄、白、绿	-40℃-85℃	
29	CXO12864E	128*64	73.00 × 71.86 × 2.00	61.41 × 30.69	3.3V	并口/IIC/SPI	SSD1322	2.70寸	黄、白、绿	-40℃-85℃	
30	CXO128128A	128*128	25.90 × 41.20 × 1.20	20.076 × 20.076	3.3V	并口/IIC/SPI	SH1107	1.12寸	白	-40℃-85℃	
31	CXO160136A	160*136	32.70 × 54.85 × 1.20	27.18 × 23.10	3.3V	并口/IIC/SPI	SH1108	1.07寸	白	-40℃-85℃	
32	CXO25664A	256*64	82.50 × 19.00 × 1.60	51.18 × 12.78	3.3V	并口/IIC/SPI	SH1122	2.08寸	白	-40℃-85℃	
33	CXO25664B	256*64	88.00 × 47.80 × 2.00	76.78 × 19.18	3.3V	并口/IIC/SPI	SSD1322	3.12寸	蓝、黄、白、绿	-40℃-85℃	
34	CXO25664C	256*64	146.00 × 65.00 × 2.00	135.65 × 33.89	3.3V	并口/IIC/SPI	SSD1322	5.50寸	黄、绿	-40℃-85℃	